



DATE: November 8, 2021  
QUOTE #: 290493-01

CITY OF ROUND ROCK  
MARSHALL REYNOLDS

Jeffrey Kell  
512.917.3277

221 E MAIN AVE  
ROUND ROCK, TEXAS 78664-5271

One (1) New Caterpillar Inc Model: 272D3 Compact Construction Equipment with all standard equipment in addition to the additional specifications listed below:

SALE PRICE	\$58,726.00
TOTAL PRICE	\$58,726.00
<hr/>	
SUB TOTAL	\$58,726.00
TOTAL SOURCEWELL PURCHASE PRICE	\$58,726.00

**WARRANTY**

Standard Warranty: 24 Month/2000 Hour Total Machine Limited Warranty

List Price	\$75,745.00
Sourcewell discount 19%	[\$14,391.00]
Adjusted Sales Price	\$61,354.00
Dealer Prep	\$550.00
Delivery	\$350.00
Holt Cat Discount	[\$3,528.00]
TOTAL SOURCEWELL SALES PRICE	\$58,726.00

**Deliver – March 2021 includes future price increases**

**NOTES**

Includes – Open Cab, Quick coupler, and bucket

Sourcewell Contract # 032119-CAT

**MACHINE SPECIFICATIONS**

DESCRIPTION	REF.#
QP1/C1/H2/MAN-QC	512-4272
LANE 2 ORDER	0P-9002
RIDE CONTROL, NONE	512-3490
BATTERY, HEAVY DUTY, 850 CCA	568-5611
REAR LIGHTS	356-6082
SEAT BELT, 2"	542-6994
TIRES, 12/16.5 CAT 10PR	568-4634
QUICK COUPLER, MANUAL	345-4910
CERTIFICATION ARR, P65	563-1163
INSTRUCTIONS, ANSI, USA	512-4282
SERIALIZED TECHNICAL MEDIA KIT	421-8926
PACK, DOMESTIC TRUCK	0P-0210
CANOPY PACKAGE, PRO PLUS	588-9094
PRODUCT LINK, CELLULAR PL243	566-7115
FILM, SELF LEVEL, ANSI	435-9238

Bucket smooth edge or tooth

## STANDARD EQUIPMENT

---

### POWERTRAIN

Cat C3.8 turbo aftercooled diesel engine  
-Gross horsepower per SAE J1349  
98 hp (73 kW) @ 2400 RPM  
-Electric fuel priming pump  
-Air inlet heater starting aid  
-Liquid cooled, direct injection  
Air cleaner, dual element, radial seal  
S-O-S sampling valve, hydraulic oil  
Filter, cartridge type, hydraulic

Filters, canister type, fuel  
and water separator  
Radiator / hydraulic oil  
cooler (side-by-side)  
Spring applied, hydraulically released,  
parking brakes  
Hydrostatic transmission  
Four wheel chain drive

### HYDRAULICS

CONTROLS:  
Electro/hydraulic implement control

Electro/hydraulic hydrostatic  
transmission control

### ELECTRICAL

12 volt electrical system  
100 ampere alternator  
Ignition key start / stop / aux switch  
Lights:  
-Gauge backlighting

-Two rear tail lights  
-Dome light  
Backup alarm  
Electrical outlet, beacon

### OPERATOR ENVIRONMENT

Operator warning system indicators:  
-Air filter restriction  
-Alternator output  
-Armrest raised / operator out of seat  
-Engine coolant temperature  
-Engine oil pressure  
-Air inlet heater activation  
-Hydraulic filter restriction  
-Hydraulic oil temperature  
-Park brake engages  
-Engine emission system  
Gauges: DEF level, fuel level, hour  
meter and tachometer  
Storage compartment with netting  
Adjustable vinyl seat  
Ergonomic contoured armrest

Adjustable joystick controls  
Control interlock system, when operator  
leaves seat or armrest raised :  
-Hydraulic system disables  
-Hydrostatic transmission disables  
-Parking brake engages  
ROPS Cab, open, tilt up  
Anti-theft security system with 50 user  
code capability  
FOPS, Level I  
Top and rear windows  
Floormat  
Interior rear view mirror  
12V electric socket  
Horn  
Hand (dial) throttle electronic

### FRAMES

Lift linkage, vertical path  
Chassis, one piece welded  
Machine tie down points (6)  
Belly pan cleanout

Support, lift arm  
Cast rear bumper  
Ventilated rear door with integrated  
sealing

## OTHER STANDARD EQUIPMENT

Engine enclosure - lockable  
Extended life antifreeze (-37C, -34F)  
Coupler, mechanical  
Hydraulic oil level sight gauge  
Radiator coolant level sight gauge  
Radiator expansion bottle  
Cat tough guard hose

Heavy duty flat faced quick disconnects  
with integrated pressure release  
Split d-Ring to route work tool hoses  
along side of left lift arm  
Variable speed hydraulic cooling fan  
Per SAE J818-2007 and EN 474-3:2006 and  
ISO 14397-1:2007