



DATE: June 15, 2021
QUOTE #:276458-02

CITY OF ROUND ROCK
MARSHALL REYNOLDS

Jeffrey Kell
512.917.3277

221 E MAIN AVE
ROUND ROCK, TEXAS 78664-5271

One (1) New Caterpillar Inc Model: 272D Compact Construction Equipment with all standard equipment in addition to the additional specifications listed below:

STOCK NUMBER: HLK045154

SALE PRICE	\$55,228.00
TOTAL PRICE	\$55,228.00
<hr/>	
SUB TOTAL	\$55,228.00
TOTAL SOURCEWELL PURCHASE PRICE	\$55,228.00

List Price 272D3	\$71,723.00
List Price Bucket	\$1,956.00
Total List Price	\$73,679.00
Sourcewell Discount 21%	(\$15,473.00)
Adjusted Sales Price	\$58,206.00
Dealer Prep	\$550.00
Delivery	\$350.00
Holt discount for City of Round Rock	(\$3,878.00)
Total Sourcewell Purchase Price	\$55,228.00

WARRANTY

Standard Warranty: 24 Month/2000 Hour Total Machine Limited Warranty

Additional Warranty:

48 months or 2000 hours Powertrain, Hydraulics, or Technology	\$943.00
60 months or 2000 hours powertrain, Hydraulics, or Technology	\$1,086.00

Delivery – August/September 2021

NOTES

Sourcewell # 032119-CAT

Bucket –smooth edge or tooth

MACHINE SPECIFICATIONS**STOCK NUMBER: HLK045154**

DESCRIPTION	REF.#
272D3 SKID STEER LOADER	512-4272
LANE 2 ORDER	0P-9002
RIDE CONTROL, NONE	512-3490
BATTERY, HEAVY DUTY, 850 CCA	568-5611
REAR LIGHTS	356-6082
SEAT BELT, 2"	542-6994
TIRES, 12/16.5 CAT 10PR	568-4634
QUICK COUPLER, MANUAL	345-4910
CERTIFICATION ARR, P65	563-1163
INSTRUCTIONS, ANSI, USA	512-4282
SERIALIZED TECHNICAL MEDIA KIT	421-8926
PACK, DOMESTIC TRUCK	0P-0210
CANOPY PACKAGE, PRO PLUS	588-9094
HYDRAULICS, PERFORMANCE, (H2)	512-4413
CONTROL, ISO, PROP, WT	512-4115
POWERTRAIN, TWO SPEED	512-3371
LIGHTS, LED	495-1671
ROPS, OPEN (C1)	512-3366
DISPLAY, ADVANCED, LCD, CAMERA	465-3705
FAN, COOLING, DEMAND	457-3167
SEAT,AIR SUSPENSION,VINYL,HEAT	536-9739
FILM, TWO SPEED	568-4700
PRODUCT LINK, CELLULAR PL243	566-7115
FILM, SELF LEVEL, ANSI	435-9238

STANDARD EQUIPMENT

POWERTRAIN

Cat C3.8 turbo aftercooled diesel engine
-Gross horsepower per SAE J1349
98 hp (73 kW) @ 2400 RPM
-Electric fuel priming pump
-Air inlet heater starting aid
-Liquid cooled, direct injection
Air cleaner, dual element, radial seal
S-O-S sampling valve, hydraulic oil
Filter, cartridge type, hydraulic

Filters, canister type, fuel
and water separator
Radiator / hydraulic oil
cooler (side-by-side)
Spring applied, hydraulically released,
parking brakes
Hydrostatic transmission
Four wheel chain drive

HYDRAULICS

CONTROLS:
Electro/hydraulic implement control

Electro/hydraulic hydrostatic
transmission control

ELECTRICAL

12 volt electrical system
100 ampere alternator
Ignition key start / stop / aux switch
Lights:
-Gauge backlighting

-Two rear tail lights
-Dome light
Backup alarm
Electrical outlet, beacon

OPERATOR ENVIRONMENT

Operator warning system indicators:
-Air filter restriction
-Alternator output
-Armrest raised / operator out of seat
-Engine coolant temperature
-Engine oil pressure
-Air inlet heater activation
-Hydraulic filter restriction
-Hydraulic oil temperature
-Park brake engages
-Engine emission system
Gauges: DEF level, fuel level, hour
meter and tachometer
Storage compartment with netting
Adjustable vinyl seat
Ergonomic contoured armrest

Adjustable joystick controls
Control interlock system, when operator
leaves seat or armrest raised :
-Hydraulic system disables
-Hydrostatic transmission disables
-Parking brake engages
ROPS Cab, open, tilt up
Anti-theft security system with 50 user
code capability
FOPS, Level I
Top and rear windows
Floormat
Interior rear view mirror
12V electric socket
Horn
Hand (dial) throttle electronic

FRAMES

Lift linkage, vertical path
Chassis, one piece welded
Machine tie down points (6)
Belly pan cleanout

Support, lift arm
Cast rear bumper
Ventilated rear door with integrated
sealing

OTHER STANDARD EQUIPMENT

Engine enclosure - lockable
Extended life antifreeze (-37C, -34F)
Coupler, mechanical
Hydraulic oil level sight gauge
Radiator coolant level sight gauge
Radiator expansion bottle
Cat tough guard hose

Heavy duty flat faced quick disconnects
with integrated pressure release
Split d-Ring to route work tool hoses
along side of left lift arm
Variable speed hydraulic cooling fan
Per SAE J818-2007 and EN 474-3:2006 and
ISO 14397-1:2007